



PRODUCT INFORMATION Shift-p-B4Bein_TY_EN - 24.09.2018 - www.kcsa.co.za

Shift+ Base Stackable four-legged tables.

Frame consisting of partly outward-offset, welded round steel tube legs with a central casing frame of rectangular steel tube, in each case powder-coated. Partly with tube-in-tube hexagon key height adjustment (see table). Tables with 4 plastic, felt or 2C universal glide elements or with glide elements and 2 lockable casters.

Table heights acc. to DIN EN 1729 in fixed heights or with step height adjustment with hexagon screw fastening.



Table top made from melamine resin-coated chipboard with glued plastic edge or a rigid CDF fibre board or high-strength solid HPL top. The corners have 25 mm rounding.

Function: The two mirror-inverted concave-convex basic shapes can be combined in a variety of ways into circles, rows and groups. Up to 6 tables can be stacked in the park position, each table fitted with stacking protection on the underside of the casing frame.

Warning: A maximum of 3 stacked (non-loaded) tables may be moved on the casters.

The following material groups are available to choose from: Frame made of steel: M1; Top made of LIGNOpal: L4; HPL-top: L4; CDF-fibreboard: L4.

Further products on this page: PantoMove-LuPo.

	ISO/DIN EN h = 40 ○ 0 h = 53 ● 2 h = 59 ● 3 h = 64 ● 4 h = 71 ● 5 h = 76 ● 6 h = 82 ● 7			
Shift+ Base			01440 convex black	01441 concave silver
	Form			
	Cover plug			
	w-d		96,7-59,1	
	DIN EN		0-2-3-4-5-6-7	
	DIN EN height adjustable		59-82	
	other h		30	
	max. ST (stacked transportable max.)		6 (3)	